

SUPPLY SOURCES OF RECOMMENDED GROUTS, ELASTOMERIC BUTYL SEALANTS AND ADHESIVES FOR INSTALLATION OF THE POLYPROPYLENE (PP) REHAB LINER (03/09)

FLOWABLE/PUMPABLE GROUTS

SULPHATE RESISTANT GROUTS

PRODUCT: MASTERFLOW 928

BASF BUILDING SYSTEMS

889 Valley Park Dr
Shakopee, MN 55379
TEL: 800 / 433-9517
FAX: 800 / 496-6067
www.buildingsystems.basf.com
800/575/7700

**PRODUCT: PORTLAND
EXPANDING
NON-SHRINK
GROUT**

TARGET PRODUCTS LTD.
8535 East Lake Drive
Burnaby, BC
Canada V5A 2T7
TEL: 604/444/3620 or

FAX: 604/420/3616
www.targetproducts.com

**PRODUCT: FIVE STAR SPECIAL GROUT 150
FIVE STAR PRODUCTS, INC**

750 Commerce Drive
Fairfield , CT 06825
TEL: 203/336/7900
FAX: 203/336/7930
www.fivestarprouducts.com

NON-SULPHATE RESISTANT GROUTS

**PRODUCT: 1107 ADVANTAGE GROUT
DAYTON SUPERIOR
COMPANY**

777 Washington Village Dr, Suite 130
Dayton, OH 45459
TEL: 877/632/9866
800/321/7628
FAX: 937/428/9560
www.daytonsuperior.com

**PRODUCT: NC GROUT
THE EUCLID CHEMICAL**

19218 Redwood Rd
Cleveland, OH 44110
TEL: 216/531/9222 or
FAX: 216/531/9596
www.euclidchemical.com

**PRODUCT: NON-SHRINK PRECISION GROUT
QUIKRETE CEMENT & CEMENT PRODUCTS**

One Securities Center
3490 Piedmont Road, Suite 1300
Atlanta, GA 30305
TEL: 404/634/9100 or 800/282/5828
FAX: 404/842/1424
www.quikrete.com

BUTYL RUBBER PREFORMED FLEXIBLE JOINT SEALANT

(PRECAST CONCRETE TOP SECTION JOINT ONLY - CONE / FLAT TOP / CAST IRON FRAME)

(SPECIFICATION - ASTM C-990, Section 6.2 Butyl Rubber Sealant)

Henry Company, Sealants Division
1277 Boyles St.
Houston, TX 77020

Press-Seal Gasket Corporation
2424 W. State Blvd.
Fort Wayne, IN 46804

TEL: 713 / 671-2494 - 800 / 231-4549

TEL: 219 / 436-0521 - 800 / 348-

7325

FAX: 713 / 673-7714

FAX: 219 / 436-1908

www.henry.com

www.press-seal.com

PRODUCT: RU106-RUB' R-NEK "LTM"

PRODUCT: PRO-STIK

ELASTOMERIC SEALANTS - RESILIENT CURING NON SHRINK CAULK TYPE

(MECHANICAL ANCHOR PENETRATIONS AND REMEDIAL "CAULK" SEAL OF MISCELLANEOUS JOINTS OR SEAMS - 1" WIDTH OR LESS)

NOTE: The sealant manufacturer's application and surface preparation procedures (including primer) must be followed. This includes recommended maximum joint depth of 1/2" (1/4" minimum thickness) and the use of bond-breaker polyethylene closed cell foam backer rod or polyethylene bond breaker tape.

SIKA Corporation
201 Polito Ave.
Lyndhurst, NJ 07071
TEL: 800 / 933-7452
www.sikaconstruction.com

General Electric Company
260 Hudson River Road
Waterford, NY 12188
TEL: 800 / 255-8886
www.gesilicones.com

PRODUCT: SIKAFLEX 1a
Polyurethane sealant;
Use SIKAFLEX 449-203 Primer

PRODUCT: SCS 1003
Silicone sealant;
Use GE SS4179 Primer

Tremco, Incorporated
3735 Green Road
Beachwood, OH 44122
TEL: 800 / 852-8173

www.tremcosealants.com

PRODUCT: VULKEM 921

Polyurethane Sealant;

Tremco171 Primer (porous substrates)

TREMprime Non-porous primer (metal substrates)

BONDING AGENT FOR DISSIMILAR MATERIALS I.E. POLYPROPYLENE, POLYETHYLENE, FIBERGLASS, URETHANE & VARIOUS METALS ETC.

3M
Industrial Business
Industrial Adhesives and Tapes Division
3M Center, Building 21-1W-10, 900 Bush Ave
St. Paul, MN 55144-1000
TEL: 800-362-3550
www.3M.com/industrial
PRODUCT: Scotch Weld DP-8010NS

CERTIFIED POLYPROPYLENE FIELD WELDING

Northwest Concrete Waterproofing
10410 40th Ave East
Tacoma, WA 98446
Tel 253-606 4964

Global Liner Systems
PO Box 326
Spanaway, WA 98387
Tel 253 686 1114

Plastic Composites Inc.
1222 Camp Ave
Mount Dora, FL 32757
Tel 352-383-0194
www.yourpci.com

CERTIFIED INSTALLATION & APPLICATION CONTRACTORS

Northwest Concrete Waterproofing
10410 40th Ave East
Tacoma, WA 98446
Tel 253-606 4964

Global Liner Systems
PO Box 326
Spanaway, WA 98387
Tel 253 686 1114